



T5 Electro Command™

T5

T4

TD5

**ALL MID RANGE TRACTORS
FOR YOUR AGRICULTURE**





FITTING ANY WORK, ANY FARM, ANY BUDGET.

New Holland Agriculture confirms its leadership in the mid-range tractors segment, with a comprehensive and updated offering of models. From the Tier 4B T5 series, with the Electro Command™ transmission that remains the reference product in the highest power segment, earning the Best Utility title at Tractor of the Year 2017, to the new T5 series, the natural successor to the T5000 range and offering various improvements in terms of compactness, performance and competitiveness. The T4 PowerStar™ range now becomes the T4 while continuing to offer high performance and the same hallmark level of reliability, a true all-purpose workhorse around the farm. Finally, the TD5 range, bringing the perfect combination of easy management, versatility and productivity – all at a highly competitive price. At New Holland you'll find a mid-range tractor for all your needs, but with performance that's decidedly a cut above the middle of the range!

T5 Electro Command™	T5.100 T5.110 T5.120
T5	T5.75 T5.85 T5.95 T5.105 T5.115
T4	T4.55 T4.65 T4.75
TD5	TD5.85 TD5.95 TD5.105 TD5.115

T5

Electro Command™

MULTITASKING BECOMES EASIER



Shifting to the next level

The 16 x 16 Electro Command™ transmission features efficient eight speed clutchless gear changes, alongside auto road and auto field for even easier operation.



Adjustable shuttle response

Make jolts, jerks and spilled grain a thing of the past by adjusting the shuttling sensitivity.

Productivity and comfort have been improved courtesy of enhanced front suspension and uprated rear lift capacity to lift even beefier implements. Enhanced flexibility for heavier tasks with the new heavy duty axle, accommodating 38" wheels, and maximum permissible weight raised up to 8.0 tons. Superior comfort and visibility in the VisionView™ cab with the wide angle mirrors and the brightest LED lighting package. The 16 x 16 Electro Command™ transmissions means you can precision tailor your forward or reverse speed to the task in hand as it harnesses the power from the ECOBlue™ compact HI-eSCR Tier 4B engine (up to 24% more torque back up) and less fuel consumption with 40kph ECO.

Models		T5.100	T5.110	T5.120
Engine				
Cylinders/Displacement	(n°/cm³)	4/3400	4/3400	4/3400
Power - ISO 14396	[kW/hp(CV)]	73/99	79/107	86/117
Transmission				
Electro Command™		16 x 16	16 x 16	16 x 16
Electro Command™ with Creeper		32 x 32	32 x 32	32 x 32
Dimensions and weight				
Min. turn radius	(mm)	4960	4960	4960
Min. weight	(kg)	4550	4550	4550



T5

COMPLETE COMPACT COMPETITIVE



Extended flexibility and versatility

With loader ready option, 3-speed PTO to manage any implement, 4400kg rear lift capacity and a wide power, axle and transmissions choice.



Top efficiency

With best-in-class fuel consumption, 40kph ECO for fuel saving transports and Engine Speed Management with 2 speed setting to quickly cope with different tasks.

The T5 range has been designed to be the ultimate all-rounder for today's modern mixed farms. Whether it is doing loader work, working with front or rear mounted implements or travelling down the road, the T5 delivers premium features in a compact package. A multitude of customisable options from transmissions to engines, when combined with engine speed management and best-in-class fuel consumption, make the T5 a winning package.

Models		T5.75	T5.85	T5.95	T5.105	T5.115
Engine						
Cylinders/Displacement	[n°/cm³]	4/3400	4/3400	4/3400	4/3400	4/3400
Power - ISO 14396	[kW/hp[CV]]	55/75	63/86	73/99	79/107	84/114
Transmission						
Synchro Shuttle™/with Creeper		12 x 12/20 x 20	12 x 12/20 x 20	-/-	-/-	-/-
Hydraulic Powershuttle/with Creeper		12 x 12/20 x 20	12 x 12/20 x 20	-/-	-/-	-/-
Dual Command™/with Creeper		-/-	-/-	24 x 24/40 x 40	24 x 24/40 x 40	24 x 24/40 x 40
Dimensions and weight						
Turn radius with SuperSteer™	[mm]	3905	3905	3905	3905	3350
Min. weight 4WD front axle with cab	[kg]	3600	3600	3700	3700	3700

- Not available



T4

THE MOST COMFORTABLE PLACE TO BE



Powershuttle transmission

The hydraulic Powershuttle with creeper provides speeds as low as 170m/h. Clutchless direction changes come as standard.



Command Arc ergonomic console

All main controls are grouped into the Command Arc console, an ergonomic cluster that allows you to perform the most frequently used operations in comfort, thus improving productivity and reducing fatigue.

The three-model T4 range has been designed around you, to take farming comfort and productivity to a whole new level. With 58 to 75hp(CV) on tap, it's the perfect productivity partner for farmers, municipalities and other operators. Distinctive styling, responsive performance, an optional column-mounted hydraulic Powershuttle for precise loader work, and a whole host of customisable options, mean your T4 is as individual as you.

Models		T4.55	T4.65	T4.75
Engine				
Cylinders/Displacement	(n°/cm³)	4/3400	4/3400	4/3400
Power - ISO 14396	[kW/hp(CV)]	43/58	48/65	55/75
Transmission				
Synchro Shuttle™/with Creeper		12 x 12/20 x 20	12 x 12/20 x 20	12 x 12/20 x 20
Hydraulic Powershuttle/with Creeper		12 x 12/20 x 20	12 x 12/20 x 20	12 x 12/20 x 20
Dimensions and weight				
Wheelbase 4WD front axle	(mm)	2132	2132	2132
Min. weight 4WD front axle with cab	(kg)	2830	2830	2830



TD5

THE REAL VALUE OF TRADITION



Hydraulic Powershuttle

Precision loader placement is as easy as 1-2-3 with the column mounted Powershuttle.



Impressive lift capacity

Maximum lift capacity is 4700kg with two assister rams for effortless linkage work.

The traditional farming values of robust design, rugged efficiency and all-rounder simplicity are exactly what the TD5 range stands for. But this is traditional farming for the 21st century, which means offering a comfortable cab for long dairying days. A tailored range of highly efficient Tier 4A compliant Common Rail 3.4 litre F5C powerplants are standard on TD5.85 - TD5.115 models, reducing fuel consumption by 10%. The head-turning range features New Holland's distinctive styling and is also available in a ROPS version with an optional FOPS compliant canopy.

Models		TD5.85	TD5.95	TD5.105	TD5.115
Engine					
Cylinders/Displacement	[n°/cm³]	4/3400	4/3400	4/3400	4/3400
Power - ISO 14396	[kW/hp[CV]]	63/86	73/99	79/107	84/114
Transmission					
Synchro Command™		12 x 4	-	-	-
Synchro Shuttle™/with Creeper		12 x 12/20 x 12	12 x 12/20 x 12	-/-	-/-
Hydraulic Powershuttle		12 x 12	12 x 12	12 x 12	12 x 12
Dimensions and weight					
Min. turn radius	(mm)	5500	5510	5580	5580
Min. weight	(kg)	3740	3740	3740	3740

- Not available





www.newholland.com/uk - www.newholland.com/ie



The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. Bts Adv. - Printed in Italy - 07/17 - (Turin) - 170007/INB